

## **Key Features**

- 7,100 ANSI Lumens with a high native contrast ratio ensure vibrant images in large venues
- True 4K HDR delivers exceptional image clarity and detail
- Supports 21:9 aspect ratio, ideal for Microsoft Teams Rooms
- Installation flexibility: motorised focus, 1.6x optical zoom, lens shift, H/V keystone correction, and 360° projection
- Centralised LAN control for efficient management



## Product **Description**

Introducing the LS950-4K from ViewSonic's Luminous Superior Series, tailored for expansive venue displays. Featuring a robust 7,100 ANSI Lumens brightness and high native contrast through DLP technology, it delivers stunning 4K UHD visuals on screens exceeding 100 inches. Perfect for museums and educational institutions, the LS950-4K's ultra-high resolution with HDR/HLG support ensures every detail is vivid and clear, enhancing viewer engagement. With 21:9 aspect ratio support, the LS950-4K is also an ideal choice for Microsoft Teams Rooms. Its 1.6x optical zoom allows for a flexible setup to suit various installation needs, and the motorised focus, lens shift, and H/V keystone adjustment make the process a breeze. Additionally, portrait mode and 360° projection capabilities cater to more advanced requirements. Comprehensive LAN control ensures seamless integration into corporate networks. Employing advanced 3rd generation laser phosphor technology, the LS950-4K boasts a remarkable 30,000-hour lifespan, reducing maintenance costs for both business and educational institutions.

- 1. Front IR
- 2. LED Indicator
- 3. Lens
- 4. Top IR
- 5. 12V Trigger
- 6. IR In
- 7. USB-B (Service)
- 8. HDBaseT
- 9. RJ-45 10. HDMI 2.0/HDCP 2.2 x2
- 11. HDMI Out
- 12. 3D Sync In
- 13. 3D Sync Out
- 14. USB-A (5V/1.5A)
- 15. Audio Out
- 16. RS232 17. Keypad

**Visit Us** www.viewsonic.com

SPECIFICATION		OTHERS	
Native Resolution:	3840x2160	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Brightness:	7100 (ANSI Lumens)	Dower Consumption	Normal: 450W
Brightness (Center Lumens):	7300	Power Consumption:	Standby: <0.5W
Contrast Ratio:	3000000:1	Operating Temperature:	5~40°C
Display Color:	1.07 Billion Colors	Carton:	Brown
Light Source Type:	Laser Phosphor	Net Weight:	14.1kg
Light Source Life (hours) with Normal Mode:	20000	Gross Weight:  Dimensions (WxDxH) with	18.8kg
Light Source Life (hours) with SuperEco Mode:	30000	Adjustment Foot:  Packing Dimensions:	486X433X186mm 654x563x373mm
Lens:	F=2.0-2.1, f=18.72-29.59mm	r acking billionsions.	
Projection Offset:	0%±10%	OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T- Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Hindi, Vietnamese, Greek, Hungarian, Danish,
Throw Ratio:	1.25-2.00		
Optical Zoom:	1.6X		
Digital Zoom:	0.8x-1.8x		
Image Size:	50"- 300"		
Throw Distance:	1.36-13.42m (100"@2.78m)		Norwegian. Total 25 languages
Keystone:	H:+/-30° , V:+/-30°		English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
Lens Shift V. Range:	+55%, -55%	User Guide Language:	
Lens Shift H. Range:	+25%, -25%		
Audible Noise (Normal):	34dB		
Audible Noise (Eco):	32dB		
Input Lag:	16ms	STANDARD ACCESSORY	
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)	Power Cord:	1
HDTV Compatibility:	576i, 576p, 720p, 1080i, 1080p, 2160p	Remote Control:  QSG:	(w/ backlit) Yes
Horizontal Frequency:	15K- 135KHz	Warranty Card:	Yes (CN Only)
Vertical Scan Rate:	23- 240Hz	Wallanty Gara.	res (or omy)
INPUT			
HDMI:	2 (HDMI 2.0/ HDCP 1.4/2.2)		
3D VESA (Sync):	1 (BNC)		
HDBaseT:	1		
IR In:	1		
OUTPUT			
HDMI out:	1		
Audio-out (3.5mm):	1		
Speaker:	10W x2		
USB Type A (Power):	1 (5V/1.5A)		
12V Trigger (3.5mm):	1		
3D SYNC Out:	1		
CONTROL			
RS232 (DB 9-pin male):	1		
RJ45 (LAN control):	1		
HOD Town D (O amain and)	4		
USB Type B (Services):	1		