ViewSonic PX749-4K 4,000 ANSI Lumens 4K Home Projector - Datasheet - ViewSonic Global



## Key Features

- Designed for Xbox for the ultimate gaming experience
- Immersive audiovisual enjoyment with 4K HDR and Harman-tuned speaker
- Up-to-300" screen size with 4,000 ANSI Lumens to maximize fun at home
- 4.2ms Ultra-Fast Input & 240Hz high refresh rate
- Direct big-screen streaming via USB-C



## Product **Description**

The PX749-4K is a 4,000 ANSI Lumens 4K home projector designed for Xbox, driving the ultimate gaming experience with Xboxexclusive resolution and refresh rate combinations. The projector shines in value and brightness as well as delivers pixelperfect visuals in true 4K UHD clarity with HDR/HLG support. Boasting a Harman-tuned speaker, the PX749-4K elevates audiovisual enjoyment, so you can fully lose yourself in the game. Experience a whole new level of playing with 4.2ms Ultra-Fast Input, a 240Hz refresh rate, and USB-C connectivity for direct streaming from Nintendo® Switch. Set up faster and easier than ever with 1.3x optical zoom, warping, H/V keystone and auto V keystone, capable of creating a screen of up to 300" on any surface. PX749-4K is also a perfect addition to your smart home, with LAN control capability that's compatible with home automation systems and 12V trigger output.

> 1. Zoom/Focus Ring 2. Power Key 3. Keypad 4. Adjustment Foot 5. Lens 6. Front IR 7. Audio Out

8. HDMI 2.0/ HDCP2.2 x 2 9. USB-C (5V/1A) 10. RS232 11. 12V Out 12. USB-A (5V/1.5A, Service) 13. RJ45 14. AC In 15. Kensington Lock



www.viewsonic.com



ViewSonic PX749-4K 4,000 ANSI Lumens 4K Home Projector - Datasheet - ViewSonic Global

Native Resolution:3840.x160Power Supply Voltage:100-240V+/- 10%, 50/60HzBrightness:4000 (ANSI Lumens)Power Consumption:Normal: 310WContrast Ratio with SuperEco1000-11Operating Temperature:0-40°CDisplay Color:1.07 Billion ColorsCarton:BrownLight Source Ufe (hours) with SuperEco Mode:4000Carton:3.0kgLight Source Life (hours) with SuperEco Mode:20000Mellight:3.0kgLight Source Life (hours) with SuperEco Mode:20000Packing Dimensions:415x168x297mmProjection Offset:120%+/.6%Packing Dimensions:415x168x297mmProjection Offset:1.3x.Packing Dimensions:415x168x297mmPojection Offset:0.75m.9.76mPacking Dimensions:415x168x297mmDigital Zoom:0.75m.9.76mNormal:307.300*Throw Diatance:0.75m.9.76mNormal:Japanese, Trickin, Portugezee, Finnish, Indonesian, Finnish, Indonesian, Cereman, Italian, Japanese, Trickin, Portugezee, Finnish, Indonesian, Cereman, Italian, Japanese, Trickin, Portugezee, Finnish, Indonesian, Cereman, Italian, Japanese, Total 24Audible Noise (Normal):336StattagAudible Noise (Normal):336StattagAudible Noise (Normal):336StattagAudible Noise (Normal):337.400*YesHDTV Compatibility:16K/15K/14Remote Control:1HDTV Compatibility:16K/15K/14Remote Control:1HDMI:(ifWIA:0.10 Cerem)	SPECIFICATION			
Bightness:4000 (ANSI Lument)Power Supply Voitage:(AC in)Contrast Flatio with SuperEco12000-1Power Consumption:Normal Silow Silomdby: 0.5 WDisplay Color:1.07 Billion ColorsCarton:BrownLight Source Type:240W UHP LampNort Weight:3.0kgLight Source Life (hours) with SuperEco Mode:3000Carcos:SoleyLight Source Life (hours) with SuperEco Mode:0000Carcos:SoleyLight Source Life (hours) with SuperEco Mode:2000Carcos:SoleyLight Source Life (hours) with SuperEco Mode:1.3-1.47Packing Dimensions:415x168x297nmProjection Offsat:1.3-4.7Packing Dimensions:415x168x297nmThrow Ratio:0.5x-2.0xSoleySoleySoleyDigital Zoom:0.5x-2.0xSoleySoleySoleyImage Size:0.5x-2.0xSoleySoleySoleyMudible Noise (Kormai):3.3dBSoleySoleySoleyAudible Noise (kormai):3.3dBSoleySoleySoleyAudible Noise (kormai):3.3dBSoleySoleySoleyHDTV Compatibility:16%13KKzSoleySoleySoleyHOY:(Maley, 576), 578, 728 (Soley, 1704kh)SoleySoleySoleyHDTV Compatibility:16%13KKzSoleySoleySoleySoleyHDTV Compatibility:16%143KabSoleySoleySoleySoleyUst Sape Calo:1(m)SoleySoley		2040-2400		400 0401/1 400/ 50/0011-
Contrast Ratio with SuperEco Mode:     12000:1     Power Consumption:     Normal Standby: -0.5W       Diplay Color:     1.07 Billion Colors     Carlon:     Brown       Light Source Ure (hours) with Sommal Mode:     4000     Carlon:     Brown       Light Source Life (hours) with SuperEco Mode:     4000     Gross Weight:     3.9kg       Light Source Life (hours) with SuperEco Mode:     759-92     Packing Dimensions:     415x168x297m       Projection Offset:     120%+/.6%     Dimensions (WXDXH) with Adjustment Foot:     318x222x108mm       Projection Offset:     1.3x.     Packing Dimensions:     415x168x297m       Policial Zoom:     0.8x-2.0x     French, Spanish, Thai, Kosen, German, Budial Zoom:     French, Spanish, Thai, Scen, Torkish, Portuguese, Enricita, Indonesian, Innis, Spanish, Traish, Portuguese, Enricita, Arabio: 24 Hanguages     English, French, Spanish, Thai, Scen, Torkish, Portuguese, Enricita, Arabio: 24 Hanguages       Audible Noise (Kormal):     3.3dB     Social Carlon:     English, Scenh, Torkish, Portuguese, Enricita, French, Spanish, Thai, Scenh, Torkish, Portuguese, Enricita, Arabio: 24 Hanguages       Mude Lag:     VolA(640 x480) to 4K(3804     VolA(640, X480) to 4K(3804)     Yource Carlon:     English, French, Spanish, Thai, Scenh, Torkish, Portuguese, Enricita, French, Spanish, Thai, Scenh, Torc			Power Supply Voltage:	
Display Color:     1.07 Billion Colors     Operating Temperature:     0-40°C       Light Source Type:     240W UHP Lamp     Carton:     Brown       Light Source Life (hours) with SyperEco Mode:     4000     Carton:     Brown       Light Source Life (hours) with SyperEco Mode:     20000     Dimensions (WXDXH) with SyperEco Mode:     3.9kg       Light Source Life (hours) with SyperEco Mode:     120%+7.6%     Dimensions (WXDXH) with Packing Dimensions:     415x168x297mm       Projection Offset:     120%+7.6%     Packing Dimensions:     415x168x297mm       Projection Offset:     1.3x     Packing Dimensions:     415x168x297mm       Digital Zoom:     0.8x-2 0x     Packing Dimensions:     415x168x297mm       Digital Zoom:     0.75m-9.76m     Throw Distance:     0.75m-9.76m     Throw Tristin, Parotace, French, Serman, Italian, Norean, Cereman, Italian, Secchinese, T.     Chrinese, Infolian, Arabic, Caren, Pollan, Varian, Spanish, Thristin, Sorean, Pollan, Varian, Caren, Pollan, Varian, Spanish, Thristin, Sorean, Pollan, Varian, Caren, Pollan, Varian, Spanish, Thristin, Sorean, Pollan, Varian, Caren, Pollan, Varian, Caren, Pollan, Varian,	Contrast Ratio with SuperEco		Power Consumption:	
Light Source Type:     240W UHP Lamp     Carton:     Brown       Light Source Life (hours) with Normal Mode:     4000     So keight:     3.9kg       Light Source Life (hours) with SuperEco Mode:     20000     Dimensions (WXDXH) with Adjustment Foot:     312k222x108mm       Lens:     F=1.94-2.12, f=12-15.6mm     Packing Dimensions (WXDXH) with Adjustment Foot:     312k222x108mm       Projection Offset:     120%-6%     Dimensions (WXDXH) with Adjustment Foot:     312k222x108mm       Diptical Zoom:     1.13-147     Packing Dimensions:     415k168x297mm       Optical Zoom:     0.8k-2 0k     Packing Dimensions:     Hindin Foot, Cace, T- Chirnese, Collinges, Sollinges, Foot, Packing, Sollinges, Sollinges, Sollinges, Sollinges, Sollinges, Foot, Sollinges, Sollinge		1 07 Billion Colors	Operating Temperature:	0~40°C
Light Source Life (hours) with Normal Mode:4000Net Weight:3.0kgLight Source Life (hours) with SuperEco Mode:20000Gross Weight:3.9kgLight Source Life (hours) with SuperEco Mode:20000Main Source Life (hours) with Ajustment Foot:312x222x108mmLens:F=1.94-2.12, f=12-15.6mmPacking Dimensions:415x168x297mmProjection Offset:1.13-1.47Packing Dimensions:415x168x297mmDigital Zoom:1.3.8OSD Language:Fanglish, French, Spanish, Thail, Kozen, German, Thail, Kozen, German, Thail, Kozen, T. Chinese, S-Chinese, S-Chinese, Uitch, Polish, Cozen, T. Chinese, S-Chinese, S-Chinese, Indonesian, Finish, Indonesian, Finish, Portuguese, Ensish, Indonesian, Finish, Nedish, Avabic, Cozen, T. Chinese, S-Chinese, Indonesian, Finish, Nedish, Turkish, Arabic, Cezen, T.Tailan, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Cezen, T.Tailan, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Cezen, T.Tailan, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Cezen, T.Tailan, Japanese, Total 20 languagesResolution Support:15K-135KH2Power Cord:1HDTV Compatibility:4000, 400, 576, 676, 720, 1080, 1480b, 2160p1HDMI:2 (HDMI 2.0, HDCP 1.4/2.2)Warralt Card:1HDMI:2 (HDMI 2.0, HDCP 1.4/2.2)Warralty Card:1USB Type C:1 (sty/2.4)LampLight Source:RLC-127USB Type A (Power):1 (sty/1.5A)LUSB Type A (Power):<			Carton:	Brown
Normal Mode:4000Gross Weight:3.8kgLight Source Life (hours) with SuperEco Mode:20000Adjustment Foot:312x22x108mmLight Source Life (hours) with SuperEco Mode:212%±1.2 [=12-15.6 mmPacking Dimensions (WXDXH) with Adjustment Foot:312x22x108mmProjection Offset:120%±1.6 %Packing Dimensions:415x168x297mmProjection Offset:1.31-1.47Packing Dimensions:415x168x297mmOptical Zoom:0.35x0.55m-9.76m (100°@2.50m)Packing Dimensions:Hoursee, Tarkin, Portugiese, Funkish, Indonese, Tinkia, Krabic, Vietnamese, Greek, Total 24 languagesNurbu Distance:0.75m-9.76m 			Net Weight:	3.0kg
SuperEco Mode:     20000     Adjustment Foot:     312222X108mm       Lens:     F=1.94-2.12, f=12-15.6mm     Packing Dimensions:     415x168x297mm       Projection Offset:     1.03-1.47     Packing Dimensions:     415x168x297mm       Optical Zoom:     1.13-1.47     Packing Dimensions:     English, French, Spanish, Takorean, German, Italian, Rusean, Towe, Turkish, Orean, German, Italian, Rusean, Towe, Turkish, Partinguese, Finish, Indonesian, India, Arabic, Otor, Vietnamese, Greek, Total 22 languages       Throw Distance:     0.75m-9.75m     State       Addible Noise (Normal):     333B     English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Rusian, Sue, Turkish, Portuguese, Finish, Tench, German, Italian, India, Arabic, Otor, Turkish, Portuguese, Finish, Tench, German, Italian, Rusian, Sue, Turkish, Portuguese, Finish, Tench, German, Italian, India, Stabic, Otor, Turkish, Portuguese, Finish, Tench, German, Italian, Stabic, Caceh, Turkish, Portuguese, Finish, Tench, German, Italian, Rusean, Tennish, Arabic, Otor, Turkish, Portuguese, Finish, Tench, German, Italian, Corean, Turkish, Portuguese, Finish, Tench, German, Italian, Rusean, Tennish, Portuguese, Finish, Tench, German, Turkish, Portuguese, Finish, Tench, German, Turkish, Portuguese, Finish, Tench, German, Italian, Rusean, Tennish, Portuguese, Finite, Core, Turkish, Portuguese, Finite		4000	Gross Weight:	3.9kg
Projection Offset:120%+/.6%Throw Ratio:1.13-1.47Optical Zoom:1.3xDigital Zoom:0.8x-2.0xImage Size:30°.300°Throw Distance:0,75m-9.76m(100°@2.50m)33dBAudible Noise (Normal):33dBAudible Noise (Eco):28dBInput Lag:4.2msResolution Support:26d(64 x 480) to 4K(3840 x 2160)HOTV Compatibility:1860; 4800; 5761; 576p, 720; 1080; 2160pHOTV Compatibility:15K-135KHzHOTV Compatibility:15K-135KHzHOMI:2 (HOMI 2.0, HDCP 1.4/2.2)Madia-out (3.5mm):1Audio-ut (3.5mm):1Audio-ut (3.5mm):1Spaceker:10W CubeUSB Type A (Power):1 (SV1.5A)12V Trigger (3.5mm):112R45 (LAN control):112R45 (LAN c		20000		312x222x108mm
Throw Ratio:1.13-1.47Optical Zoom:1.3xDigital Zoom:0.8x-2.0xImage Size:30°-300°Throw Distance:0.75m-9.76m (100°@2.50m)Keystone:+tr/-40°, V:+/-40°Audible Noise (Normal):33dBAudible Noise (Normal):33dBAudible Noise (Coc):28dBInput Lag:4.2msResolution Support:VGA(640 x 480) to 4K(3840 x 2160)HDTV Compatibility:15K-135KHzHDTV Compatibility:15K-135KHzVertical Scan Rate:23-240HzNPUT23-240HzVertical Scan Rate:23-240HzNPUT1MDN:1Spasker:1Audio-out (3.5mm):1Audio-out (3.5mm):1Spasker:1Audio-out (3.5mm):1Spasker:110% Cube1USB Type A (Power):112W Trigger (3.5mm):112W Trigger (3.	Lens:	F=1.94-2.12, f=12-15.6mm	Packing Dimensions:	415x168x297mm
Throw Ratio:1.13-1.47Optical Zoom:1.3xDigital Zoom:0.8x-2.0xImage Size:30°-300°Throw Distance:()75m-9.76m (100°g2.50m)Keystone:H-1/-40°, V.+/-40°Audible Noise (Normal):33d8Audible Noise (Normal):33d8Audible Noise (Eco):28dBInput Lag:4.2msHDTV Compatibility:4501, 4800, 5761, 576p, 7200, 10801, 1080p, 2160pHDTV Compatibility:15K-135KHzVertical Scan Rate:23-240HzVertical Scan Rate:23-240HzVertical Scan Rate:21-240HzVertical Scan Rate:1MDMI:1Audio-out (3.5mm):1Audio-out (3.5mm):1Spaker:10W CubeUSB Type A (Power):111Vertuger Scame):112V Trigger (3.5mm):112V	Projection Offset:	120%+/-6%	OSD Language:	Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T- Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish,
Optical Zoom:1.3xOSD Language:Chinese, 5-Chinese, Japanese, Jurkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 24 languagesDigtal Zoom:0.75m-9.76m (100°(22.50m)English, S-Chinese, T. Chinese, T. Chinese, Indonesian, India, Arabic, Vietnamese, Greek, Total 24 languagesKeystone:H:+/-40°, V.+/-40°Audible Noise (Normal):33dBFreed, Greema, Italian, Japanese, Korean, Polish, Portuguese, Russian, Polish, Portuguese, Russian, Vietnamese, Total 20 languagesAudible Noise (Eco):28dBFreed, Greema, Italian, Japanese, Korean, Polish, Portuguese, Russian, Vietnamese, Total 20 languagesInput Lag:4.2msFreed, Greema, Italian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20 languagesHDTV Compatibility:480i, 480p, 576i, 576p, 720p, 1800i, 1080p, 2160pPower Cord:1HDTV Compatibility:15K-135KHzPower Cord:1Wertical Scan Rate:23-240HzQSG:YesVBT(HDMI 2.0, HDCP 1.4/2.2)QSG:YesUSB Type C:1(5V/2A)QSG:YesDUTPUT1(SV1.5A)Yes (CN Only)DUTPUT1(SV1.5A)Yes (CN Only)Spaker:100 CubeYes (CN Only)USB Type A (Power):1(SV1.5A)12V Trigger (3.5mm):1Christian12V Trigger (3.5mm):112V Trigger (3.5mm):112V Trigger (3.5mm):112V Trigger (3.5mm):112V Trigger (3.5mm):112V Trigger (3.5mm):112V Trig	Throw Ratio:	1.13-1.47		
Digital Zoom:0.8x-2.0xDefend on the set of	Optical Zoom:	1.3x		
Image Size:30 -300Vietnamese, Greek, Total 24 languagesThrow Distance:0.75m-9.76m (00°22.50m)English, S-Chinese, T- Chinese, Indonesian, FinnisKeystone:H:+/-40°, V:+/-40°Audible Noise (Normal):33dBAudible Noise (Eco):28dBAudible Noise (Eco):28dBInput Lag:4.2msResolution Support:VGA(640 x 480) to 4K(3840 x 2160)HDTV Compatibility:480i, 480p, 576i, 576p, 720p 1600)HDTV Compatibility:15K-135KHzVertical Scan Rate:23-240HzVertical Scan Rate:23-240HzVBTV2 (HDMI 2.0, HDCP 1.4/2.2)USB Type C:1 (SV/2A)DUTPUT1 (SV/2A)Speaker:10W CubeUSB Type A (Power):1 (SV/1.5A)12V Trigger (3.5mm):1 (SV/1.5A)12V Trigger (3.5mm):1 (SV/1.5A)12V Trigger (3.5mm):1 (SV/1.5A)12V Trigger (3.5mm):1 	Digital Zoom:	0.8x-2.0x		
Throw Distance:0.7 bm s/ ofm (0/022.50m)Keystone:H:+/-40°, V:+/-40°Audible Noise (Normal):33dBAudible Noise (Eco):28dBLiput Lag:4.2msResolution Support:VGA(640 x 480) to 4K(3840 x 2160)HDTV Compatibility:480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160pHDTV Compatibility:15K-135KHzVertical Scan Rate:23-240HzVertical Scan Rate:23-240HzVB Type C:1 (SV/2A)USB Type C:1 (SV/2A)Audio-out (3.5mm):1Audio-out (3.5mm):1LAudio-out (3.5mm):112V Trigger (3.5mm):112V Trigger (3.5mm):1Res232 (DB 9-pin male):1145 (LAN control):1155 Euro A (Scanison):11155 Euro A (Scanis	Image Size:	30"-300"		
Reystone:H:H-40 ', V:H-40'Audible Noise (Normal):33dBAudible Noise (Normal):33dBAudible Noise (Eco):28dBLinput Lag:4.2msResolution Support:VGA/G40 x 480) to 4K(3840 x 2160)HDTV Compatibility:480i, 480p, 576i, 576p, 720p 1080i, 1080p, 2160pHDTV Compatibility:15K-135KHzVertical Scan Rate:23-240HzVertical Scan Rate:23-240HzUSB Type C:1 (5V/2A)USB Type C:1 (5V/2A)OUTPUT1Audio-out (3.5mm):1Audio-out (3.5mm):112V Trigger (3.5mm):113V 45 (LAN control):114V 5000000000000000000000000000000000000	Throw Distance:			languages
Audible Noise (Normal):33dBJapanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20 languagesAudible Noise (Eco):26dBInput Lag:4.2msResolution Support:VGA(640 x 480) to 4K(380 x) 1600, 4800, 576i, 576p, 72cp, 1080i, 1080p, 2160pHDTV Compatibility:60i, 480p, 576i, 576p, 72cp, 1080i, 1080p, 2160pHorizontal Frequency:15K-135KHzVertical Scan Rate:2240HZVertical Scan Rate:2240HZMDMI:CasciVestical Scan Rate:2Vertical Scan Rate:2MDMI:1(bV/2A)USB Type C:1(bV/2A)Varianty Card:Ves (CN ONIy)OUTPUT1(bV/2A)Audio-out (3.5mm):1Audio-out (3.5mm):1(bV/1.5A)12V Trigger (3.5mm):112V Trigger (3.5mm):112V Trigger (3.5mm):1Res232 (DB 9-pin male):112N Trigger (3.5mm):112N Trigger (3.5mm):1 <td>Keystone:</td> <td>H:+/-40°, V:+/-40°</td> <td rowspan="4">User Guide Language:</td> <td rowspan="4">Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20</td>	Keystone:	H:+/-40°, V:+/-40°	User Guide Language:	Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20
Audible Noise (Eco):28dBSpanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20 languagesInput Lag:4.2msStantak, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20 languagesResolution Support:VGA(640 x 480) to 4K(3840 x 2160)Stantamese, Total 20 languagesHDTV Compatibility:480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160pPower Cord:1Horizontal Frequency:15K-135KHzPower Cord:1 (1m)Vertical Scan Rate:23-240HzQSG:YesNPUT(HDMI 2.0, HDCP 1.4/2.2)Warranty Card:Yes (CN Only)HDMI:(HDMI 2.0, HDCP 1.4/2.2)Warranty Card:Yes (CN Only)USB Type C:1 (5V/2A)Lamp/Light Source:RLC-127OUTPUT1Carry Bag:PJ-WMK-007Audio-out (3.5mm):1Carry Bag:PJ-CASE-008Speaker:10W CubeCarry Bag:PJ-CASE-008USB Type A (Power):111Control:1CONTROL1R2322 (DB 9-pin male):11StantamHDR Turk (LAN control):11StantamHDR Turk (LAN control):1<	Audible Noise (Normal):	33dB		
Input Lag:4.2msVietnamese, Total 20 InguagesResolution Support:VGA(640 x 480) to 4K(3840 x 2160)FATNDARD ACCESSORYHDTV Compatibility:800i, 480p, 576i, 576p, 720p 1080i, 1080p, 2160pPower Cord:1HDTV Compatibility:15K-135KHzPower Cord:1(1m)Vertical Scan Rate:23-240HzRemote Control:1(w' backlit)NPUT23-240HZQSG:VesNPUTVertical Scan Rate:1(5V/2A)Varranty Card:Ves (CN Only)NBMI:1(5V/2A)Lamp/Light Source:RLC-127Valio-out (3.5mm):1Carry Bag:PJ-CASE-008Speaker:10W CubeCarry Bag:PJ-CASE-008USB Type A (Power):11Vertical Source:Vertical Source:R232 (DB 9-pin male):11Vertical Source:Vertical Source:R233 (DB 9-pin male):11Vertical Source:Vertical Source:R234 (LAN contro):11Vertical Source:Vertical Source:R234 (L	Audible Noise (Eco):	28dB		
Resolution Support:VGA(640 x 480) to 4K(3840 x 2160)STANDARD ACCESSORYHDTV Compatibility:480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160pPower Cord:1HDTV Compatibility:15K-135KHzPower Cord::1Vertical Scan Rate:23-240HzRemote Control:1Vertical Scan Rate:23-240HzOSG:YesINPUTCase:Yes (CN Only)HDMI:1(V/2A)Varranty Card:Yes (CN Only)USB Type C:115V/2A)Lamp/Light Source:RLC-127OUTPUT1Vall/Ceiling Mount:PJ-WMK-007Audio-out (3.5mm):1Carry Bag:PJ-CASE-008Speaker:10W CubeServer Source:Very Bag:Very Bag:USB Type A (Power):11Very Bag:Very Bag:Very Bag:RS232 (DB 9-pin male):11Very Bag:Very Bag:Very Bag:RS232 (DB 9-pin male):11Very Bag:Very Bag:HSB Type A (Sourison):11Very Bag:Very Bag:RS232 (DB 9-pin male):11Very Bag:Very Bag:HSB Type A (Sourison):11Very Bag:Very Bag:HUSB Type A (Sourison)	Input Lag:	4.2ms		
HDTV Compatibility:4800, 5760, 5760, 7200, 10800, 2160pUSB-C Cable:1 (1m)Horizontal Frequency:15K-135KHzRemote Control:1 (im)Vertical Scan Rate:23-240HzQSG:VesINPUTCSG:YesVesHDMI:2 (HDMI 2.0, HDCP 1.4/2.2)Warranty Card:Yes (CN Only)USB Type C:1 (5V/2A)Mamp/Light Source:RLC-127OUTPUT1Carry Bag:PJ-WKK-007Audio-out (3.5mm):1Carry Bag:PJ-CASE-008Speaker:10W CubeVery Bag:Very Bag:Very Bag:USB Type A (Power):1 (5V/1.5A)Very Bag:Very Bag:Very Bag:12V Trigger (3.5mm):1SecondVery Bag:Very Bag:RS232 (DB 9-pin male):11Very Bag:Very Bag:Very Bag:12V Trigger (Alon control):11Very Bag:Very Bag:12V Trigger (Seminer):11Very Bag:Very Bag:12V Trigger (Alon control):1Very Bag:Very Bag:Very Bag:13V Trigger (Alon control):1Very Bag:Very Bag:Very Bag:14UBB Every (Control):1Very Bag:Very Bag:Very Bag:14UB Every (Control):1Very Bag:<	Resolution Support:		STANDARD ACCESSORY	languagee
Horizontal Frequency:15K-135KHzUSB-C Cable:1 (1m)Horizontal Frequency:15K-135KHzRemote Control:1 (w/ backlit)Vertical Scan Rate:23-240HzQSG:YesINPUT2 (HDMI 2.0, HDCP 1.4/2.2)Warranty Card:Yes (CN Only)USB Type C:1 (5V/2A)Uamp/Light Source:RLC-127OUTPUT1Wall/Ceiling Mount:PJ-WMK-007Audio-out (3.5mm):1Carry Bag:PJ-CASE-008Speaker:10W CubeVarranty Card:Very Bag:USB Type A (Power):1 (5V/1.5A)Seaker:PJ-CASE-00812V Trigger (3.5mm):1Seaker:Seaker:RS232 (DB 9-pin male):11Itse E type A (Samiaca):1Itse E type A (Samiaca): <td< td=""><td>HDTV Compatibility:</td><td></td><td>Power Cord:</td><td>1</td></td<>	HDTV Compatibility:		Power Cord:	1
Vertical Scan Rate:23-240HzRemote Control:(w/ backlit)INPUTQSG:YesHDMI:2 (HDMI 2.0, HDCP 1.4/2.2)Warranty Card:Yes (CN Only)USB Type C:1 (5V/2A)Lamp/Light Source:RLC-127OUTPUT1Val/Ceiling Mount:PJ-WMK-007Audio-out (3.5mm):1Carry Bag:PJ-CASE-008Speaker:10W CubeCarry Bag:PJ-CASE-00812V Trigger (3.5mm):1State of the second s	· ·		USB-C Cable:	1 (1m)
INPUTQSG:YesHDM: $\partial_{HDM1 2.0, HDCP 1.4/2.0}$ Warranty Card:Yes (CN Only)USB Type C:1 (5V/2A)Imp/Light Source:RLC-127Audio-out (3.5mm):1Yang All (Ceiling Mount:PJ-WMK-007Speaker:10W CubeCarry Bag:PJ-CASE-008USB Type A (Power):1 (5V/1.5A)YesYes12V Trigger (3.5mm):1YesYesRS232 (DB 9-pin male):1YesYes12W Tupo A (Control):1YesYes12W Tupo A (Control):1YesYes <tr< td=""><td>. ,</td><td></td><td>Remote Control:</td><td>•</td></tr<>	. ,		Remote Control:	•
HDMI:2 (HDMI 2.0, HDCP 1.4/2.2)Warranty Card:Yes (CN Only)USB Type C:1 (5V/2A)Hamp/Light Source:RLC-127OUTPUT1Vall/Ceiling Mount:PJ-WMK-007Audio-out (3.5mm):1Carry Bag:PJ-CASE-008Speaker:10W CubeCarry Bag:FUUSB Type A (Power):1Stort 1.5A)Fu12V Trigger (3.5mm):1FuFuRS232 (DB 9-pin male):1FuFu12V Trupe A (Servineo):1FuFu120 Tupe A (Servineo):1FuFu120 T		23-24002	QSG:	
HDMI:   (HDMI 2.0, HDCP 1.4/2.2)     USB Type C:   1 (5V/2A)     OUTPUT   Lamp/Light Source:   RLC-127     Audio-out (3.5mm):   1     Speaker:   10W Cube     USB Type A (Power):   1 (5V/1.5A)     12V Trigger (3.5mm):   1     RS232 (DB 9-pin male):   1     RS232 (DB 9-pin male):   1     ILSE Type A (Control):   1     ILSE Type A (Control):   1		2	Warranty Card:	Yes (CN Only)
OUTPUTNumber of the second	HDMI:		OPTIONAL ACCESSORY	
Audio-out (3.5mm):1Carry Bag:PJ-CASE-008Speaker:10W CubeUSB Type A (Power):1 (5V/1.5A)12V Trigger (3.5mm):1RS232 (DB 9-pin male):1RJ45 (LAN control):11	USB Type C:	1 (5V/2A)	Lamp/Light Source:	RLC-127
Speaker:10W CubeUSB Type A (Power):1 (5V/1.5A)12V Trigger (3.5mm):1RS232 (DB 9-pin male):11RJ45 (LAN control):11	OUTPUT		Wall/Ceiling Mount:	PJ-WMK-007
USB Type A (Power):   1 (5V/1.5A)     12V Trigger (3.5mm):   1     CONTROL   1     RS232 (DB 9-pin male):   1     RJ45 (LAN control):   1     USB Type A (Services):   1	Audio-out (3.5mm):	1	Carry Bag:	PJ-CASE-008
12V Trigger (3.5mm): 1 CONTROL RS232 (DB 9-pin male): 1 RJ45 (LAN control): 1 USB Ture 4 (Services): 1	Speaker:	10W Cube		
CONTROL   RS232 (DB 9-pin male):   1   RJ45 (LAN control):   1	USB Type A (Power):	1 (5V/1.5A)		
RS232 (DB 9-pin male):   1     RJ45 (LAN control):   1     USB Ture 4 (Services):   1	12V Trigger (3.5mm):	1		
RJ45 (LAN control): 1	CONTROL			
	RS232 (DB 9-pin male):	1		
	RJ45 (LAN control):	1		
	USB Type A (Services):			

