

USB-C Multiport Adapter with HDMI - USB 3.0 Port - 60W PD - Black

Product ID: CDP2HDUACP



This USB-C multiport adapter with HDMI lets you add vital connections to your MacBook or Windows laptop, through a single USB-C port.

For maximum productivity, connect your USB-C or Thunderbolt 3 laptop to a 4K 30Hz monitor, using this USB-C to 4K HDMI adapter. You can also connect to an HDMI projector or TV in a boardroom or other meeting space, to deliver presentations on a shared screen.

The USB-C adapter lets you power and charge your USB-C laptop during a presentation or while you're working, with a USB-C Power Delivery port. Even if your laptop has only a single USB-C port available, you can keep your laptop powered.

This USB-C multiport adapter offers a USB 3.0 port that's backward compatible with older USB devices - ideal for data transfers, syncing, or charging your mobile devices.

The compact all-in-one adapter is a vital accessory for your USB-C laptop. With its small-footprint design, you can take it with you anywhere you would use your laptop.

CDP2HDUACP is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Note: To ensure full adapter functionality, your laptop's USB-C port must support USB Power Delivery and DP Alt Mode.

Certifications, Reports and Compatibility







Applications

- Multitask faster with an additional, 4K HDMI monitor
- Deliver presentations from your laptop on an HDMI TV or projector
- Connect to an HDMI TV in a hotel or hoteling/hot desk space

Features

• CONNECT TO 4K HDMI: This USB C multiport adapter with HDMI lets you connect your USB-C laptop to a 4K UHD HDMI external monitor (4096 x 2160 resolution at 24Hz or 3840 x 2160 @ 30Hz). It's the ideal accessory for a MacBook or other USB-C laptop

• POWER AND CHARGE: The USB-C adapter with charging supports Power Delivery 2.0 (up to 60W), so you can use your laptop's USB-C power adapter to power and charge your laptop

• CONNECT A USB DEVICE: The all-in-one adapter lets you connect a peripheral device like a flash drive or mouse using the USB 3.0 (Type A) port. The USB port is backward-compatible so you can still connect your existing USB device

• TRAVEL-FRIENDLY DESIGN: The compact design lets you carry the portable USB C HDMI multiport adapter with you wherever you go

• THE IT PRO'S CHOICE: Designed and built for IT Professionals, this USB Type C multiport adapter is backed for 3 Years, including free lifetime 24/5 multi-lingual technical assistance

Hardware		
	Warranty	3 Years
	4K Support	Yes
	Fast-Charge Port(s)	No
	Displays Supported	1
	Bus Type	USB-C
	Industry Standards	USB 3.0 - Backward compatible with USB 2.0 and
	Chipset ID	VIA/VLI - VL100
		VIA/VLI - VL210





Parade - PS176

Performance	Maximum Data Transfer Rate	5 Gbps (USB 3.0)
	Maximum Digital Resolutions	4096 x 2160p @ 24Hz / 3840 x 2160p @ 30Hz
		Lower resolutions are also supported.
	Type and Rate	USB 3.0 - 5 Gbit/s
	UASP Support	Yes
Connector(s)		
	Connector Type(s)	1 - USB 3.2 Type-C (24 pin, Gen 1, 5Gbps)
		1 - USB Type-C (24 pin) USB Power Delivery Only
		1 - HDMI (19 pin)
		1 - USB Type-A (9 pin, 5 Gbps)
Special Notes / Requirements		
	System and Cable Requirements	A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support USB Power Delivery 2.0 and DP alt mode).
		Optional: USB-C power adapter (for example, your laptop's USB-C based power adapter).
	Note	Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery 2.0 and DP alt mode.
		The adapter can connect to a host laptop's USB-C port that doesn't support USB Power Delivery 2.0. However, in this configuration if a power adapter is connected to the multifunction adapter, it will not pass power through to your host laptop.
		A 4K-capable display is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K)
		USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps.
Power		
	Power Source	USB-Powered
	Power Delivery	60W



	Output Voltage	5 DC
Environmental	Operating Temperature Storage Temperature	0C to 40C (32F to 104F) -20C to 70C (-4F to 158F)
	Humidity	0~90% RH (Non-condensing)
Physical Characteristics		
	Color	Black
	Material	Plastic
	Cable Length	4.0 in [101 mm]
	Product Length	2.4 in [60 mm]
	Product Width	2.0 in [5 cm]
	Product Height	0.4 in [1.1 cm]
	Weight of Product	1.2 oz [35 g]
Packaging Information		
	Package Quantity	1
	Package Length	6.6 in [16.8 cm]
	Package Width	5.7 in [14.6 cm]
	Package Height	1.3 in [32 mm]
	Shipping (Package) Weight	4.4 oz [126.0 g]
What's in the Box	Included in Package	1 - USB-C to 4K HDMI multifunction adapter

*Product appearance and specifications are subject to change without notice.