

105 Touch  
105 Non-Touch

81 Touch  
81 Non-Touch



# Pana 21:9 Displays



## Pana 21:9 Displays

- **21:9 in 5K**
- **Touch and Non-Touch versions**
- **Preloaded with SimpleShare®**

### See the World through a 21:9 Lens

Pana's 21:9 ultra-wide 5K resolution brings a refreshing form factor to the conventional display market. Our 8-foot wide Pana 105 canvas optimizes team productivity allowing for improved interaction and work place collaboration.

The market most receptive to this format are enterprise and industrial companies leaning into visualization technology to be their focal point and center piece. CIOs are telling us 21:9 is making the biggest impressions enabling them to stand out, land new clients and attract better talent. That's a win-win.

Lightweight and maneuverable, the Pana is ideal for retrofits as all sizes fit into a commercial service elevator and can be mounted using standard industry hardware without reinforced concrete or steel backing. Pana's lower infrastructure costs equates to a lower cost of ownership as a result of easy retrofit, reduced energy consumption and affordable price point.

### PANA FEATURES

#### 21:9 Panoramic

The extra wide form factor is inspired by our natural human ability to see wider than we see taller.

#### 5K Resolution

Pana provides 33% more pixels with 5K resolution giving the user more real estate in which to work.

#### Touch User Experience

We formed the addiction to touch interaction by interacting with our phone. Touch enables the expectation for interactive autonomy, speed and ease-of-use. Pana interactive displays are touch driven by multiple, simultaneous collaborators. Former collaboration sessions using a mouse and keyboard driven by one person now seems linear and limiting.

#### Built for Human Interaction

More pertinent information gets placed in our visual sweet spot increasing our comprehension and productivity. And all the pixels are placed where everyone on the team can reach them preserving our dignity among our peers of not having to overreach or bend over to interact with the display.

#### Interactivity through SimpleShare®

Jupiter's SimpleShare enables intuitive interaction optimized for Pana displays. The platform provides quick and easy access to your daily workflow.

# Pana 21:9 Displays

	Pana 105 Touch	Pana 105 Non-Touch	Pana 81 Touch	Pana 81 Non-Touch
<b>SPECIFICATIONS</b>				
Resolution	5120 x 2160	5120 x 2160	5120 x 2160	5120 x 2160
Orientation	Landscape and Portrait	Landscape and Portrait	Landscape and Portrait	Landscape and Portrait
Screen Size	105" ( 2667 mm) diagonal	105" ( 2667 mm) diagonal	81" (2057 mm) diagonal	81" (2057 mm) diagonal
Backlight Technology	DLED with local dimming	DLED with local dimming	DLED with local dimming	DLED with local dimming
Contrast Ratio	1 8 0 0 : 1	1 8 0 0 : 1	1 8 0 0 : 1	1 8 0 0 : 1
Brightness	450 cd/m <sup>2</sup>	450 cd/m <sup>2</sup>	450 cd/m <sup>2</sup>	450 cd/m <sup>2</sup>
Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz
Viewing Angle	178° H/V	178° H/V	178° H/V	178° H/V
Lifetime	≥ 50,000 Hrs	≥ 50,000 Hrs	≥ 50,000 Hrs	≥ 50,000 Hrs
Response Time	8 ms	8 ms	8 ms	8 ms
Display	21:9 aspect ratio, anti-glare, IPS LCD, direct-bonding IR with 20 simultaneous touch points	21:9 aspect ratio, anti-glare, IPS LCD	21:9 aspect ratio, anti-glare, IPS LCD, bezel-less metal-mesh capacitive with 20 simultaneous touch points	21:9 aspect ratio, anti-glare, IPS LCD
Stylus	Optional	N/A	Optional	N/A
OPS Slot	Yes	No	Yes	No
<b>POWER</b>				
Input Current	6A	6A	6A	6A
Power Standby	≥ 0.5 W	≥ 0.5 W	≥ 0.5 W	≥ 0.5 W
Speaker Output	2 x 16 W	2 x 16 W	2 x 15 W	2 x 15 W
Avg Power Consumption	140 W	140 W	140 W	140 W
Max Power Consumption	600 W	600 W	500 W	500 W
USB-C PD Output	65W	65W	65W	65W
Operating Temperature	32°F - 104°F (0°C - 40°C)	32°F - 104°F (0°C - 40°C)	32°F - 104°F (0°C - 40°C)	32°F - 104°F (0°C - 40°C)
<b>CONNECTIVITY</b>				
DisplayPort 1.4 In	1	1	1	1
DisplayPort 1.4 Out	1	1	1	1
HDMI In	2	1	2	1
USB-C with 65w	1	1	1	1
USB 2.0 Type-A	4	4	4	4
3.5mm Line Out	1	1	1	1
S/PDIF Optical Fiber	1	1	1	1
100M Ethernet	1	1	1	1
RS232 / RJ45	1	1	1	1
<b>DIMENSIONS</b>				
Dimensions	99.2" x 43.5" x 4.3" (2519 mm x 1105 mm x 110 mm)	96.5" x 40.7" x 3.7" (2450 mm x 1034 mm x 94 mm)	76.1" x 33.3" x 3.4" (1933 mm x 847 mm x 86 mm)	75.6" x 32.7" x 3.3" (1919 mm x 830 mm x 83 mm)
Weight	209.4 lbs (95 kg)	136.7 lbs (62 kg)		77.2 lbs (35 kg)
Shipping Dimensions	109.4" x 59" x 13" (2780 mm x 1500 mm x 330 mm)	105.5" x 55.1" x 12.6" (2680 mm x 1400 mm x 320 mm)		
Shipping Weight	275.6 lbs (125 kg)	187.4 lbs (85 kg)		
VESA Mount Dimensions	1500 mm x 500 mm	1500 mm x 500 mm	800 mm x 400 mm	800 mm x 400 mm
Power Cable	9.8 ft (3m)	9.8 ft (3m)	9.8 ft (3m)	9.8 ft (3m)



jupiter.com